



PLC-WL2500

- Brightness: 2500ANSI Lumen
- Resolution: WXGA (1280 x 800)
- Short throw Projector, 80" diagonal image @ 86cm
- Long life air filter, up to 4000 hours
- 10w built in audio amplifier and speaker
- Screen aspect Ratio selection, 4:3, 16:9, 16:10
- Security Bar (Will accept up to a 10mm cable)

PLC-WL2500

TECHNICAL DETAILS	
Category	PLC-WL2500 Business and Education
Panel	0.59" Polysilicon TFT (16:10)
Lamp	230w
Brightness ANSI lumens	2500 (Normal Mode), 1900 (Eco Mode)
Lamp Service Life	4000h (Eco Mode), 3000h (Normal Mode)
Fan Noise	29dBA (Eco Mode), 36dBA (Normal Mode)
Standard Lens	F=1.8, f=6.68mm
Throw Distance Ratio	0.50:1
Throw Distance	0.64m – 1.2m
Contrast Ratio	500:1
Resolution in pixels	1280 x 800
Image size min–max (diagonal)	60" – 110"
Uniformity	80%
Bandwidth/Frequency	140MHz, Horizontal 15kHz – 100kHz, Vertical 50Hz – 100Hz
Colour Systems	NTSC, PAL, SECAM, NTSC4.43, PAL-M, PAL-N
Connections	Inputs: 2 x Dsub15 (1 switchable to monitor out) 1 x HDMI 1 x S-video 1 x RCA (composite Video) Audio: 1 x Mini Jack 2 x RCA 1 x Mini Jack (Audio out) Control: 1 x D-sub9 (RS232) 1 x RJ45 (LAN)
Keystone Correction	Vertical ±20°
HDTV Signals	480p, 575p, 720p (50/60), 1080i (50/60), 1080p (50/60)
Computer Compatibility	WUXGA, WSXGA+, WXGA+, WXGA, UXGA, SXGA+, XGA, SVGA, VGA
Zoom/Focus	Manual focus
Power Consumption/Voltage	217w (Eco Mode), 316w (Normal Mode), 0.78w (Standby Mode)
Warranty	3 year
Dimensions (W x H x D)	350 143 x 382mm
Weight	4.6kg
Standard Accessories	Owners Manual (CD ROM), Power Cable, Remote Control, Computer Cable (Dsub15 – Dsub15)
Optional Accessories	POA-CA-COMPVGA (Component – VGA Cable), POA-CA SCART (Scart – VGA Cable)

* You can use the distance calculator at www.uk.sanyo.com to determine exact image sizes and distances



Technical specifications subject to change without notice. Status 05/2010

